

PRODUCT NAME **ETHANOL DENATURED 100AG.F.3**
SUPPLIER **AJAX FINECHEM Ph:(02) 9524 0757; 1300 884 078 Emerg. Ph:1800 638 556 (24 hr) Aust / (NZ): 0800 154**

CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA
CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No.	1170	Hazchem Code	2YE	Pkg Group	II
DG Class	3	Subsidiary Risk(s)	None Allocated	EPG	3A1
Poison Schedule	None Allocated				

HEALTH HAZARDS

Eye Irritant. Contact may result in irritation, lacrimation, pain and redness.

Inhalation Irritant. Over exposure may result in irritation of the nose and throat, coughing and headache. High level exposure may result in nausea, dizziness and drowsiness.

Skin Irritant. Contact may result in drying and defatting of the skin, rash and dermatitis. May be absorbed through skin with harmful effects.

Ingestion Low to moderate toxicity. Ingestion may result in gastrointestinal irritation, nausea, vomiting, abdominal pain, diarrhoea, headache, dizziness and drowsiness with large quantities. Chronic exposure may result in liver damage.

FIRST AID

Eye If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre (PIC) or a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre (PIC) or a doctor.

Ingestion For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

PRECAUTIONS

Flammability Highly flammable. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Vapour may form explosive mixtures with air. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights etc. when handling. Earth containers when dispensing fluids.

Reactivity Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), alkalis (eg. hydroxides), heat and ignition sources.

Ventilation Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

PERSONAL PROTECTIVE EQUIPMENT

Wear splash-proof goggles and neoprene or nitrile gloves. When using large quantities or where heavy contamination is likely, wear: coveralls. Where an inhalation risk exists, wear: a Type A (Organic vapour) respirator. At high vapour levels, wear: an Air-line respirator or self Contained Breathing Apparatus (SCBA).

